

PRODUCT OVERVIEW

INDUSTRIAL LUBRICATION

revision 03/2013




Table of contents

► Single Line Lubrication Systems

► Gear pump units	01-1-10-05
► Pneumatic pump units	01-1-10-07
► Hydraulic pump units	01-1-10-08
► Manual piston pumps	
► Proportioning valves, metering valves	01-1-10-09
► Metering distributor block, Metering unit	01-1-10-10
► Distributor strips	01-1-10-11
► Single line distributor (NV, UEN, IV)	

► Progressive Central Lubrication Systems

► Progressive distributors	01-1-10-12
(MX-F, MX-I, LX-2, LX-3, SX-1, SX-2, SX-3, SX-5, UX, SXE-2, SXE-2R, SXE-3, SXD, SXW-1, SXW-2)	

► Dual Line Central Lubrication Systems

► Dual line distributors (BV, BW, BZ, UXZ)	01-1-10-13
► Components for main line controlling	
► Components for change-over monitoring	

► Piston pumps

► Oil Lubrication Pumps

► Series TDM	01-1-10-14
► Series A	01-1-10-15
► Series D	
► Series C	01-1-10-16
► Series OKG - electric drive	01-1-10-17
► Drive electro magnetic (K 407, K 412, K 442, K 400, MP 2646)	
► Drive pneumatic (P2663, P2664, P2669, P2686, PAU)	01-1-10-18
► Drive mechanic single piston-tappet pump (EHS) or tappet pump (SP)	
► Drive hydraulic (FAZ02142-05, FAZ02142-06)	

► Grease Lubrication Pumps

► Series FK (FKR, FKP, FKG, FKG-V, FKG-S, FKG-A)	01-1-10-19
► Series FK and FVAM (FKGM, FKMS, FVAM) - electric drive	
► Series PICO - electric drive	01-1-10-20
► Series FK...-OC / FK...-EP - electric drive or rotating	01-1-10-21
► Series F (F6, F-super, F-super 3)	01-1-10-22
► Drive electro magnetic (MP-2643)	01-1-10-23
► Drive mechanic (FHX-2, FH-2535, FHX, FHX-MX)	
► Drive pneumatic (P-2103, PP-1)	
► Drive hydraulic (HP-1, PH-2104, HKP-1, HPM-2, HPH-2)	01-1-10-24

► Circulating Lubrication Systems

► Flow control valve, Flow limiting device, Volume flow control FXE	01-1-10-25
► Gear pumps	01-1-10-26
► Internal gear pumps	

► Special lubrication systems

► Barrel pumps (EFP-1, EFPM-2, HFP-3U, Qmaxx)	01-1-10-27
► Lubrication pinions for gears	01-1-10-28

▶ PU-lubrication pinion for gearings and chains	01-1-10-28
▶ Special units	01-1-10-29
▶ Oil-air units	01-1-10-30
▶ Oil-air mixing distributor	
▶ Accessories	
▶ Oil reservoir	01-1-10-31

Gear pump units



EA 1,5



BEKA
Xlube

Model	Type	Delivery volume (l/min)	Oper. pressure max. (bar)	Reservoir content (l)	Reservoir material	Lubricant	Operating voltage
EA 1,5 oil	2727	0,4	40	3	plastic, transparent	oil, 20 - 700 mm ² /s	400 V AC / 3~
EA 1,5 fluid grease	2728					fluid grease a/t release list	
BEKA Xlube	2712	0,25	28	1,2		oil, 20 - 700 mm ² /s or fluid grease a/t release list	230 V AC



Super 3
EA-tronic left



Super 3
EA-tronic right



Super EA-tronic
with 4 l-reservoir



Super EA-tronic
with 6 l-reservoir



Mini EA-tronic
with 3 l-reservoir



Mini 2
EA-tronic

Model	Type	Delivery volume (l/min)	Oper. pressure max. (bar)	Reservoir content (l)	Reservoir material	Lubricant	Operating voltage
Super 3 EA-tronic left	2805	0,4	35	3	plastic, transparent	oil 20 - 700 mm²/s or fluid grease acc.to release list	115 V AC 230 V AC 24 V DC
Super 3 EA-tronic right	2806						
Super EA-tronic with 4 l-reservoir	2800			4	aluminium		
Super EA-tronic with 6 l-reservoir				6	steel		
Mini EA-tronic with 3 l-reservoir				3	plastic, transparent		
Mini 2 EA-tronic	2810			1,5			115 V AC 230 V AC

Overview

Gear pump units



ES ES 2711 with 3 l-reservoir ES 2711 with 6 l-reservoir ES 2711 with 13 l-reservoir ES 2711 with 16 l-reservoir ES 2711 with 30 l-reservoir

Model	Type	Delivery volume (l/min)	Oper. pressure max. (bar)	Reservoir content (l)	Reservoir material	Lubricant	Operating voltage
ES (w/o reservoir)	2710	0,4	35	-	-	oil 20 - 700 mm²/s or fluid grease acc.to release list	400 V AC / 3~
ES 2711 with 3 l-reservoir	2711			3	aluminium		
ES 2711 with 6 l-reservoir				6	steel		
ES 2711 with 13 l-reservoir				13	aluminium		
ES 2711 with 16 l-reservoir				16	steel		
ES 2711 with 30 l-reservoir				30	aluminium		



EA 3 EA 3 / EA 6 with 3 l-reservoir EA 3 / EA 6 with 6 l-reservoir EA 3 / EA 6 with 13 l-reservoir EA 3 / EA 6 with 16 l-reservoir EA 3 / EA 6 with 30 l-reservoir

Model	Type	Delivery volume (l/min)	Oper. pressure max. (bar)	Reservoir content (l)	Reservoir material	Lubricant	Operating voltage
EA 3 / EA 6 (without reservoir)	2700	1 or 2	35	-	-	oil 20 - 700 mm²/s	400 V AC / 3~
EA 3 / EA 6 with 3 l-reservoir	2705			3	aluminium		
EA 3 / EA 6 with 6 l-reservoir				6	steel		
EA 3 / EA 6 with 13 l-reservoir				13	aluminium		
EA 3 / EA 6 with 16 l-reservoir				16	steel		
EA 3 / EA 6 with 30 l-reservoir				30	aluminium		

Subject to alterations!

© BEKA 2013 All rights reserved!

Pneumatic pump units



P30.2 to P50.8
with reservoir



2564
with 2,7 l-reservoir



P30-6
with 6 l-reservoir



P5.2 / P8.4 / P8.8
with reservoir



P5.6 / P8.6
with 6 l-reservoir

Model	Type	Delivery volume (cm ³ /stroke)	Pressure reduction	Drive press. (bar)	Reservoir content (l)	Reservoir material	Lubricant
P30.2 to P50.8	2564	30 or 50	1:9	5 - 10	2,5 / 4,2 / 8	plastic, transparent	oil 20 - 700 mm ² /s or fluid grease acc.to release list
2564 with 2,7 l-reservoir					2,7		
P30-6 with 6 l-reservoir					6	steel	
P5.2 / P8.4 / P8.8	2563	10	1:11	4 - 8	2,5 / 4,2 / 8	plastic, tr.	
P5.6 / P8.6 with 6 l-reservoir	2565	15	1:8		6	steel	



P30 and P50
without reservoir



P605
without reservoir



P5.1,2 and P8.1,2
with 1,2 l-reservoir



PPF-1
with 4 l reservoir

Model	Type	Delivery volume (cm³/stroke)	Pressure reduction	Drive press. (bar)	Reservoir content (l)	Reservoir material	Lubricant
P30 and P50 (without reservoir)	2564	30 or 50	1:9	5 - 10	-	-	Oil 20 - 700 mm²/s or fluid grease acc.to release list
P605 (without reservoir)	2566	3 9,5 15	1:32 1:12 1:8	3 - 8			
P5.1,2 and P8.1,2 with 1,2 l-reservoir		2562	10 15				
PPF-1	2161	50	1:5	6 - 10	4		

Overview

Hydraulic pump units



PH1/ PH6/ PH10
without reservoir



PH1-6 / PH6-6 / PH10-6
with 6 l-reservoir

Model	Type	Delivery volume (cm ³ /stroke)	Pressure reduction	Operating press. (bar)	Relief press. (bar)	Reservoir content (l)	Reservoir material	Lubric.
PH1 PH6 PH10 without reservoir	2577	1 6 10	1:2 1:1	max. 55	1 - 2	-	-	oil 20 - 700 mm ² /s or fluid gre. acc.to release list
PH1-6 PH6-6 PH10-6 with 6 l-reservoir	2578	1 6 10	1:2 1:1					
						6	steel	

Manual piston pumps



Manual pump 2532



Manual pump 2533

Model	Type	Delivery volume (cm ³ /stroke)	Operating press. (bar)	Reservoir content (l)	Reservoir material	Lubricant
Manual pump 2532	2532	6 / 10 / 15	30	1,2	plastic, transparent	oil, 20 - 700 mm ² /s or fluid grease acc.to release list
Manual pump 2533	2533	6 / 10				

Metering valves (dynamic system)



Size 1
with bolted connection
for pipe Ø 4



Size 1
with bolted connection
for pipe Ø 6



Size 1
with plug connection
for PA pipes



Size 1
with plug connection
for PA-pipes with chamfer

Model	Meter. volume (mm³/stroke)	Size	Type / Connection type			Relief press. (bar)	Operating press. (bar)	Metering medium
Z31ZV1	10	1	4030 / bolted connection	4036 / plug-type connection for PA-pipes	4036 / plug-type connection for PA pipes and chamfers	max. 1	15 - 40	oil 50 - 700 mm²/s or fluid grease acc.to Freigabe- liste
Z31ZV2	20							
Z31ZV3	30							
Z31ZV5	50							
Z31ZV10	100							
Z31ZV15	150	2						
Z31ZV20	200							
Z31ZV40	400	3						
Z31ZV50	500							
Z31ZV60	600							
Z31ZV100	1000							

Metering valves (static system)



Z31DV.. / Z31DDV..
with bolted connection



Z31DV.. / Z31DDV..
with plug connection



Z31DV..
with elbow plug connection

Model	Metering volume (mm ³ /stroke)	Type	Connection type	Relief press. max. (bar)	Operating press. (bar)	Material	Metering medium
Z31DV3	30	4031	- Bolted connection	4	15 - 40	steel or V2A (1.4305)	oil 20 - 700 mm ² /s or fluid grease acc.to release list
Z31DV5	50		- Plug-type conn.				
Z31DV10	100		for polyamide pipes				
Z31DV15	150		- elbow plug-type conn.				
Z31DV20	200		for polyamide pipes				
Z31DDV3	30	4032	- Bolted connection	1	12 - 40	steel	oil 20 - 700 mm ² /s
Z31DDV6	60		- Plug-type conn.				
Z31DDV10	100						
Z31DDV16	160						

Metering distributor blocks



Size 1		Size 2		Size 3										
4018		40181		4180		4181		41823		41841				
Bolted connection		Plug connection		Bolted connection		Plug connection		Bolted connection		Plug connection				
Size	Meter.- volume (mm³/stroke)	Type Connection type	Number of lube points	Connections main line	lube line	Relief press. max. (bar)	Operating press. (bar)	Metering medium						
1	10	4018 Bolted connection	1 to 10	M10x1	M8x1 pipe Ø 4 mm	3	12 - 50	oil 10 - 1000 mm²/s or fluid grease acc.to release list						
	30													
	60													
	100	40181 Plug-type connection												
	160													
2	100	4180 Bolted connection		M12x1		4	16 - 50							
	200													
	300								4181 Plug-type connection					
	400													
	600													
3	200	41820/ 41823/ 41824 Bolted connection	1 to 3	M12x1 or G 1/8										
	400													
	600					41840/ 41841/ 41842 Plug-type connection								
	1000													
	1500													

Metering units for direct lubrication point connection (static system)



Design A		Design B		Design C		Design D			
Design	Version	Meter. volume (mm³/stroke)	Type	Connection type	Relief press. (bar)	Operating press. (bar)	Metering medium		
A	G	30 60 100	4176	Bolted connection	max. 1	max. 35	oil		
B	L						40 - 250 mm²/s		
C	T						fluid grease		
D	W						n. release list		
E (pivotable)	LS		4174	Plug-type conn. Ø 4 mm for polyamide pipes			oil		
F (pivotable)	TS						40 - 250 mm²/s		

Distributor blocks




Size 1
Z32VL3 or Z33VL6

Size 1
Z32VL4 or Z33VL8

Size 1
Z32VL5 or Z33VL10

Size	Model	Outlets	Number of outlets	Type	Connection inlets	Connection outlets	Material
1	Z32VL1 - Z32VL12	one-sided	1 to 12	4020	with or without union nut (M10x1, pipe-Ø 6, with olive)	M8x1 M10x1	steel, galv. or 1.4305
	Z33VL2 - Z33VL24	two-sided	2x1 to 2x12				
2	Z32VL1/2 - Z32VL10/2	one-sided	1 to 10			M10x1	steel, galvanized
	Z33VL2/2 - Z33VL20/2	two-sided	2x1 to 2x10				

Single line distributor



NV-6

UEN

GVO-1

IV-11 / IV-1 2-outlets

Model	Type	Operating pressure max. (bar)	Number of outlets	Inlet connection	Outlet connections	Material	Metering vol. optional (mm³ / stroke and outlet)	Metering medium
NV	4020	45	1 to 6*	M16x1,5	M8x1	Housing: GD-Zn additional part: brass	100 - 1000	oils; fluid grease NLGI 000, 00
UEN	4124	300	1 to 12**	G 1/4	M10x1	steel, ZnNi-coating acc. to DIN 50979	25 - 400	fluid grease; grease up to NLGI 2
GVO-1	4126	120	1 to 15	M10x1	M8x1		16 - 50	oil; fluid grease NLGI 000, 00
IV-1	4125	240	1 to 6	G 3/8	G 1/8	steel, galvanized	200 - 1200 adjustable	fluid grease, grease up to NLGI
				NPT 3/8"	NPT 1/8"			
IV-11				G 3/4	G 1/4		1000 - 11000 adjustable	
				NPT 3/4"	NPT 1/4"			

* no. of outlets can be enlarged when combining


** no. of outlet can be enlarged by a connection element

© BEKA 2013 All rights reserved!

Subject to alterations!

Overview

Disk construction



Model	Type	Number of rev. max. (revol./min)	Operat. press. max. (bar)	No. of outlets max.	Inlet connection	Outlet connection	Material	Metering vol. optional (mm³ /stroke and outlet)	Meter- medium
MX-F	4010	180	300	24	M10x1	M10x1	steel, galv.	25 - 105	oils and greases up to NLGI-cl. 2
MX-I	3979	60		16			1.4404	45 - 105	
LX-2	3972	180		20			steel, ZnNi	200	
LX-3	3973	60					1.4404 1.4401		
SX-1	4000	180			G 1/8	G 1/8	steel, galv.	68 - 430	
SX-2	3989	60					1.4301	75 - 470	
SX-3	4008								
SX-5	3983	180		G 3/8	G 1/4	steel, galv.	1130 - 2000		
UX	4005	250		G 1/2	G 3/8				

Segment construction

Sandwich construction



SXE-2 / SXE-2R (with return)

SXE-3

SXD

SXW-1

SXW-2

Model	Type	No. of revol. max. (revol./min)	Oper. press. max. (bar)	No. of outlets max.	Inlet connection	Outlet connection	Material	Meterin vol. optional (mm³ / stroke and outlet)	Metering medium
SXE-2	4003	180	300	20	G 1/4	G 1/8	steel, galvanized	100 - 760	oils and greases up to NLGI 2
SXE-2R	3971					M11x1			
SXE-3	3985		200		G 3/8	G 1/4			
SXD	3998					G 3/8			
SXW-1	3977		150		G 1/4	G 1/4	steel, galv.,	100 - 900	
SXW-2	3978						connec. plate, aluminium	900 - 3700	

Dual line distributors



BV



BW



BZ



UXZ

Model	Type	Operating pressure max. (bar)	No. of outlets max.	Connection inlet	Connection outlet	Material	Metering volume optional (mm³ / stroke and outlet)	Metering medium
BV	3981	300	8	G 1/4	G 1/4	steel, galvanized	70 - 300	Oils and greases up to NLGI-cl. 2
BW	3980	(min. 35)		G 3/8		steel, galvaniz. or 1.4305	300 - 1500	
BZ	4001	400				250 - 3000 (regelbar)		
UXZ	4006	150	20		G 3/8	steel. galvaniz.	1130 - 2000	

For controlling the main line



4/3-way control valve



4/2-way control valve



Pressure changeover switch



Differential pressure control device



electronic pressure sensor

Component	Type	Actuation	Operating pressure (bar)	Flow volume (l/min)	Connection main line	Material	Lubricant
4/3-waycontrol valve	4340	electrical	400	8	G 1/2 G 3/4	GG-25	oils and greases up to NLGI-CI. 2
4/2-waycontrol valve	4065	electro-pneumatic	350	20	G 3/8	steel, galvanized	
Pressure changeover switch	0421	hydraulic	150 / 300	8	G 1/4		
Differential pressure control device	4305	electrical	400	-	G 3/8		
electron. press. sensor	0421					-	

Overview

Series TDM



TDM-FSU

TDM-FS 4

Model	Type	No. of outlets	Delivery volume adjustable, max. (cm³ / stroke and outlet)	Ratio	Input speed max. (rev / min)	Operating pressure max. (bar)	Suction height max. (mm)
TDM-FSU	2200	1 - 2	0,1	33:1	300 - 1800	3	300
TDM-FSU-M	2201						
TDM-FS 4	2204	3 - 4					
TDM-FS 4-M	2205						



TDM 2



TDM 4



TDM 8



TDM 4-M
230/400 V AC / 3~

Model	Type	No. of outlets	Delivery volume adjustable, max. (cm ³ / stroke and outlet)	Ratio	Input speed max. (rev / min)	Operating pressure max. (bar)	Suction height max. (mm)
TDM 2 rotating	2210	1 - 2	0,039 - 0,088	71,5:1 - 428:1	500 - 3000	3 / 5	300
TDM 2-M electric	2211						
TDM 4 rotating	2212	3 - 4					
TDM 4-M electric	2213						
TDM 8 rotating	2214	5 - 8		92:1 - 1050:1			
TDM 8-M electric	2215						
TDM-M with motor	Power requirement: 0,09 / 0,11 kW; available for all pumps of series TDM, see TDM-FSU-M, TDM-FS 4-M, TDM 2-M, TDM 4-M, TDM 8-M						

Subject to alterations!

© BEKA 2013 All rights reserved!

Series A - drive see table



Model	Type	Outlets max.	Delivery volume adjustable, max. (cm ³ / stroke and outlet)	Reduction	Input speed max. (rev / min)	Operating pressure max. (bar)	Suction height max. (mm)
AZU rotating	2240	12	0,06	8:1 / 16:1 25:1 / 50:1	200 / 400 600 / 1300	10	500
AZP oscillating	2242			1:1	40		
AF rotating	2244			18:1 / 25:1 / 36:1	500 / 600 / 1400		
AFG rotating	2248			80:1 / 160:1 / 320:1 / 640:1	2400 2800		
AFG-M elektrisch	2250			50:1 / 80:1 / 160:1 / 320:1 / 640:1	1500 / 1800		
APG-M electric	2243			400:1 / 288:1	2900 / 3000		

Series D - drive see table



Model	Type	Outlets max.	Delivery volume adjustable, max. (cm ³ / stroke and outlet)	Reduction	Input speed max. (U / min)	Operating pressure max. (bar)	Suction height max. (mm)
DU rotating	2260	12	0,15	12:1 / 18:1 / 36:1	500 - 750	50	1000
DP oscillating	2262			2:1	80		
DG rotating	2266			80:1 / 160:1 / 320:1 / 640:1	2500		
DFG rotating	2268			160:1 / 320:1 / 640:1	2500		
DFG-M electric	2270			80:1 / 160:1 / 320:1 / 640:1	Power demand 0,25 kW		

Overview

Series C - drive see table



C 1,5
oscillating



CS 3
rotating




CS 3
oscillating




CCS 3
rotating



CCS 6
oscillating



CC 30
rotating



CCS 30
oscillating

Model	Drive	Type	Out-lets max.	Deliv. volume adjustable, max. (cm³ / stroke and outlet)	Res. capacity (l)	Reduction	Input speed max. (rev / min)	Operating pressure max. (bar)			
C 1,5	rotating	2300	12	0,15	1,8 3	12/18/36 or 72:1	500/ 750/ 1400/ 2600	50			
	oscillating	2301				1:1 / 3,15:1	40 / 125				
CS 1,5	rotating	2302	6			12/18/36 or 72:1	500/ 750/ 1400/ 2600				
	oscillating	2303					1:1 / 3,15:1		40 / 125		
C 3	rotating	2310	12				12/18/36 or 72:1		500/ 750/ 1400/ 2600		
	oscillating	2311							1:1 / 3,15:1	40 / 125	
CS 3	rotating	2312	6						12/18/36 or 72:1	500/ 750/ 1400/ 2600	
	oscillating	2313								1:1 / 3,15:1	40 /125
CC 3	rotating	2320	24		3 6					12/18/36 or 72:1	500/ 750/ 1400/ 2600
	oscillating	2321								1:1 / 3,15:1	40 / 125
CCS 3	rotating	2322	12			12/18/36 or 72:1				500/ 750/ 1400/ 2600	
	oscillating	2323								1:1 / 3,15:1	40 / 125
CC 6	rotating	2340	24				12/18/36 or 72:1			500/ 750/ 1400/ 2600	
	oscillating	2341								1:1 / 3,15:1	40 / 125
CCS 6	rotating	2342	12						12/18/36 or 72:1	500/ 750/ 1400/ 2600	
	oscillating	2343								1:1 / 3,15:1	40 / 125
CC 30	rotating	2360	48		30					12/18/36 or 72:1	500/ 750/ 1400/ 2600
	oscillating	2361								1:1 / 3,15:1	40 / 125
CCS 30	oscillating	2362	24			1:1 / 3,15:1				40 / 125	
	rotating	2363								12/18/36 or 72:1	500/ 750/ 1400/ 2600
CC 30 M	w. motor	2364	48				80/120/180/240/ 360 oder 720:1			1500/ 1800	
CCS 30 M	w. motor	2368	24								

Subject to alterations!

© BEKA 2013 All rights reserved!

Series OKG - electric drive



OKGGM-OC
DC

OKGGM-OC
with PSU,
115 or 230 V AC

OKGM-OC
400 V AC / 3~

OKGGM-EP
DC

OKGGM-EP
with PSU,
115 or 230 V AC

OKGM-EP
400 V AC / 3~

Model	Type	Out-lets max.	Delivery volume max. (cm ³ / stroke and outlet)	Reser. content (kg)	Reduction	Input speed motor / shaft (rev. / min)	Pump speed 1 rev. = 1 stroke (rev. / min)	Press. max. (bar)	Operating voltage
OKGGM-OC	2035	21	0,005 0,010 0,015 0,025 0,050	2,5 4,2 8,0	-	-	15	200	12 V DC 24 V DC
OKGGM-OC with PSU	2029								115 V AC 230 V AC
OKGM-OC	2017								400 V AC / 3~
OKGGM-EP	2040	3	0,06 0,12 0,17		-	-	15	350**	12 V DC 24 V DC
OKGGM-EP with PSU	2038								115 V AC 230 V AC
OKGM-EP	2011	6							400 V AC / 3~

* Special request after consultation

** Pressure limiting valve adjusted to 280 bar,

= power supply unit

Electro magnetic drive



K-407

K-412

K-442

K-400 or MP-2646

Model	Type	Outlets	Delivery volume max. (cm ³ / stroke and outlet)	Reservoir capacity (l)	Reservoir material	Duty ratio	Operating voltage
K-407	2652	1 - 6	0,040 0,100	0,75	plastic	40 %	24 V DC
K-412	2653			1,2			
K-442	2640			4,2			
K-400	2654			without reservoir	-	25 %	230 V AC
MP-2646	2641						24 V DC 180 V DC

© BEKA 2013 All rights reserved!

Subject to alterations!

Pneumatic drive



P2663



P2669

Model	Type	Outlets max.	Delivery volume max. (cm ³ / stroke and outlet)	Reservoir content (l)	Reservoir material	Pressure ratio	Drive press. (bar)
P-2663	2663	5	0,025	0,5	plastic	1:20	6 - 10
P-2664	2664			1,2			
P-2669	2669		0,010	0,5			
P-2686	2686	4	0,005 - 0,015	-	-	1:84	
			0,025 - 0,050			1:47	
PAU	2685	1	10			1:20	

Mechanic drive



EHS 0,6 / EHS 0,15 S55

Model	Type	Outlets max.	Delivery volume max. (cm³ / stroke and outlet)	Operating press. max. (bar)	Suct. height max. (mm)
EHS 0,6	2140	4	0,15	12	300
EHS 0,15 S55	2141	1		80	-
SP 0,56	2605		0,56		
SP 1.12			1.12		

Hydraulic drive



FAZ02142-05



FAZ02142-06

Model	Type	Outlets max.	Delivery volume max. (cm ³ /stroke and outlet)	Operating pressure max. (bar)	Drive pressure (bar)
FAZ02142-05	2122	10	2 / 3 / 4,5 / 6 / 7,5	200	60 - 200
FAZ02142-06		1	6		

Subject to alterations!

© BEKA 2013 All rights reserved!

Series FK - drive see table



FKR
rotating



FKP
oscillating



FKG
rotating
vertical



FKG-V
rotating
pivotable by 90°



FKG-S
rotating
vertical



FKG-A
rotating
vertical

Model	type	Outlets max.	Delivery volume adjustable, max. (cm ³ / stroke and outlet)	Reser. capacity (kg)	Reduction	Input speed (rev / min)	Press. max. (bar)
FKR rotating	2000	12	0,1	1 1,5 2 4	14:1 / 19:1 / 28:1 / 57:1	min.: 28/38/56/114 max.: 210/300/430/850	50
FKP oscillating	2001				3,5:1	35	
FKG rotating vertical	2002				84:1 / 150:1 / 300:1 / 400:1 / 600:1 / 1200:1	300 - 2800	
FKG-V rotating pivotable by 90°	2004				84:1 / 150:1 / 300:1 / 400:1 / 600:1 / 1200:1		
FKG-S rotating vertical	2005						
FKG-A rotating vertical	2006	8		300:1 / 450:1 / 900:1			

Series FK and FVAM - electric drive



FKGM
with motor



FKMS
with motor



FVAM
with motor


Model	Type	Out-lets max.	Delivery volume adjustable, max. (cm³/h and outlet)	Reservoir capacity (kg)	Reduction	Input speed (rev / min)	Operating press. max. (bar)	Operating voltage
FKGM with motor	2007	12	0,1	1	84:1 / 150:1 / 300:1 / 400:1 / 600:1 / 1200:1	1420	50	230 / 400 V AC / 3~
FKMS with motor	2008			1,5 2 4		at 50 Hz		400 V AC / 3~
FVAM with motor	2030	8	0,15	1 / 1,5 / 2 / 4 / 10	420:1 / 560:1 / 750:1	1700 at 60 Hz	100	230 / 400 V AC / 3~

PICO - electric drive



Model	Type	Out-lets max.	Deliv. volume max. (cm ³ / stroke and outlet)	Reservoir content (kg)	System type	Pump speed 1 rev. = 1 stroke (rev. / min)	Operating press. max. (bar)	Operating voltage
PICO	2185	8	0,005 / 0,010 / 0,015 / 0,025 / 0,05	1,2	multi line	15	200	12 V DC 24 V DC
		2	0,12		progressive		280	

Series FK...-OC / FK...-EP - electric or rotating drive



Model	Type	Outlets max.	Delivering volume max. (cm³ / stroke and outlet)	Reser. capa- city (kg)	Reduction	Input speed motor / shaft (rev / min)	No. of pump rev. 1 rev. = 1 stroke (rev / min)	Press. max. (bar)	Operating voltage
FKGGM-OC	2154	21	0,005 0,010 0,015 0,025 0,050	1,9 2,5 4,2 8,0	-	-	15	200	12 V DC 24 V DC
FKGGM-OC with PSU	2024								115 V AC 230 V AC
FKGM-OC	2016				400 V AC / 3~				
FKGGM-EP	2018	3	0,06 0,12 0,17	1,9 2,5 4,2 8,0	-	-	15	350**	12 V DC 24 V DC
FKGGM-EP with PSU	2037								115 V AC 230 V AC
FKGGM-EPC with control	2036								100 V bis 250 V AC
FKGM-EP	2013	6			(80:1)* / 150:1 / 300:1 / 400:1 / 600:1 / 1200:1	1350 at 50 Hz 1600 at 60 Hz	-		400 V AC / 3~
FKGM-EP with norm motor	2014	8				1500 at 50 Hz 1800 at 60 Hz			
FKG-EP with flange 56 C acc. to NEMA rotating					(2 / 4 steel)	-	min. 1 max. 25		-
FKR-EP rotating	2015	7		14:1 / 19:1 / 28:1 / 57:1					

* special requests after consultation

** Pressure limiting valve adjusted to max. 280 bar

© BEKA 2013 All rights reserved!

Subject to alterations!

Series F - drive see table



F6
rotating



F6
with geared motor



F-super
with geared motor



F-super
rotating



F-super 3
with geared motor



F-super 3
oscillating

Model	Type	Out-lets max.	Delivery volume max. (cm³ / stroke and outlet)	Reserv. content (kg)	Reduction	Input speed motor / shaft (rev. / min)	Pump speed 1 rev. = 1 stroke (rev. / min)	Press. max. (bar)	Operating voltage
F6 rotating	2032	20	0,06 0,12 0,17	5 7,5 10	9:1 / 18:1 / 25:1 / 36:1 / 50:1	-	min. 1 max. 25	250	-
F6 w. geared motor	2034				135:1 / 270:1 / 375:1 / 450:1 / 540:1 / 600:1 / 750:1 / 900:1 / 1250:1/1800:1/ 2500:1	2800 at 50 Hz 3300 at 60 Hz	-		230 / 400 V AC / 3~
F-super w. geared motor	2050			21	88:1 / 165:1 / 280:1 / 410:1 / 600:1 / 800:1 / 1000:1	1420 at 50 Hz 1700 at 60 Hz	min. 1 max. 25		-
F-super rotating	2051	15:1 / 22,5:1 / 45:1				-		-	
oscillating	2052				2,5:1				
F-super 3 w. geared motor	2053	3 (4=	0,56	48 100	46:1	1420 at 50 Hz 1700 at 60 Hz	-	400	230 / 400 V AC / 3~
F-super 3 rotating	2054	Special version			15:1 / 22,5:1 / 45:1	-	min. 1 max. 25		-
oscillating	2055				2,5:1				

Electro-magnetic



Model	Type	Outlets max.	Delivery volume max. (cm ³ / stroke and outlet)	Reservoir content (l)	Reservoir material	Duty ratio	Operating voltage
MP-2643	2643	1 - 6	0,015 / 0,025 / 0,035	0,4	plastic, transparent	25 %	24 V DC

Mechanic drive



FHX-2



FH-2535



FHX



FHX-MX with MX

Model	Type	Outlets	Delivery volume max. (cm ³ / stroke)	Reserv. content (l)	Reservoir material	Pressure max. (bar)
FHX-2	2534	1	1,5	1,2	plastic, transparent	300
			3			150
FH-2535	2535	1	1,5	1 / 1,5 / 2 / 3 / 4 (kg)	steel	300
			3			150
FHX	2081	1	2	0,4 (kg)	cartridge	400
FHX-MX (w. progre. distributor MX-F)						300

Pneumatic pumps



P2103



PP-1

* pressure limiting valve adjusted to 280 bar

** at drive pressure 8 bar

Model	Type	Outlets max.	Delivery volume max. (cm ³ / stroke and outlet)	Reservoir content (kg)	Reservoir material	Drive	Pressure ratio	Drive pressure (bar)
P-2103	2103	1	2	1,2	plastic, transparent	1:32	250**	4 - 8
			4	1 / 1,5 / 2 / 3 / 4	steel	1:18	140**	
			6			1:10	80**	
PP-1	2153	3	0,06 - 0,17	1,9 / 2,5 / 4,2 / 8	plastic, transparent	-	350*	6 - 10
				2 / 4	steel			

Hydraulic drive



HP-1



PH-2104



HKP-1



HPM-2



HPH-2

Model	Type	Out-lets	Delivery vol. (cm ³ /stroke and outlet)	Reservoir content (kg)	Reservoir material	Operating press. max. (bar)	Drive pressure (bar)
HP-1	2163	1 - 6	0,06 - 0,17	1,9 / 2,5 / 4 / 8	plastic, transparent	350*	30** - 250
				2 / 4	steel		
PH-2104	2104	1	1 / 2 / 3 / 4 / 6	1,2	plastic, transparent	280*	25 - 160
				1 / 1,5 / 2 / 3 / 4	steel		
HKP-1	2120	2	1	2,5	plastic, transparent	(min. 60) - 250	85 - 275
HPM-2	2574	1	0,2 - 2,0	0,4	cartridge	100 - 220	130 - 250
HPH-2	2574		0,1 - 1,0			250 - 350	ab 100

* pressure limiting valve adjusted to 280 bar

** min. drive pressure depends on counterpressure of lubrication system

Flow control valve



Type	Operating pressure (bar)	Pressure drop (bar)	Volume flow (l/min)	Material	Weight (kg)	Lubricant
4060	10 - 250	7	0,1 - 8	steel	1,65	oils 10 - 1000 mm ² /s

Flow limiting device



Type	Operating pressure (bar)	Pressure drop (bar)	Volume flow (l/min)	Material	Weight (kg)	Lubricant
4365	5 - 200 (without add-ons)	≥ 5	1,15 - 3,00 (dep. on orifice disc-Ø)	steel	0,39	oils ON synt. a. mineral. basis 20 - 600 mm ² /s


Volume flow control



Model	Type	Oper. pressure max. (bar)	Volume flow (l/min)	Meßvolume (cm ³)	Material	Weight (kg)	Lubricant
FXE 250 with conn. plate without conn. plate	4063 4064	250	0,05 - 12	1,2	steel (cover Al)	0,7 + 0,85	Oils 20 - 1000 mm ² /s

Overview


Gear pumps



Flange pumps



Foot pump



Motor pumps
horizontal



Motor pumps
vertical

Series	Pump type	Delivery volume (l/min)	Operating pressure max. (bar)
FL 0,5	flange pumps	0,06 - 3,00	35
MZ 0,5	motor pumps, horizontal		
MZE 0,5	motor pumps, vertical		
FL 0	flange pumps	0,25 - 2,40	50
MZ 0	motor pumps, vertical		
FL 1 to 5	flange pumps	1 - 65	30
U 1 to 5	foot pumps		
MZN 1 to 5	motor pumps, horizontal		
MZE 1 to 5	motor pumps, vertical		


Internal gear pumps




FLI and UI



FLIS and UIS




MZIR



MZI

Series	Pump type	Delivery volume (l/min)	Operating pressure max. (bar)
FLI and UI Connections radial	Flange and foot pumps	4 - 32	100
FLIS and UIS Connections at front			
MZIR Connections radial	Motor pumps		
MZI Connections at front			



EFP-1

EFPM-2

HFP-3U
(complete)

HFP-3U
(w/o pump cover,
w/o follower piston,
w/o visual level sensor)

Qmaxx 2
with hoist
with hand crank

Qmaxx
with electric hoist

PFP-...-U

Model	Type	Drive	Delivery vol. max. (cm³ / stroke)	Barrel size (kg)	Operating voltage	Drive pressure (bar) / -volume (l/min)	Operat. press. max (bar)
EFP-1	2196	electric	0,33	20 / 25 / 50 / 200	24 V DC	-	300*
EFPM-2	2197				115 V AC	-	
HFP-3U with or without pump cover, follower piston, level sensor	2198	hydraulic	26		230/400 V AC/3~	-	35 bis 60 / max. 4,5
Qmaxx 2	2179	hydraulic	9000 (cm³/min)	200	-	max. 100 / max. 40	100
Qmaxx	2187	electric	3000 / 9000 (cm³/min)		400/500 V AC/3~	-	
PFP-...-U	2690	pneumatic	26	20 / 25 / 50 / 200	-	4 - 6 / max. 134	300*

* pressure limiting valve adjusted to max. 280 bar

** pressure limiting valve adjusted to max. 300 bar

Overview

Segmented lubrication pin. for gears



Lubrication pinion for gears



PU-lube pinion for gears




PU-lube pinion for chains



Material lubrication pinion	Segmented lubrication pinion for gears	Lubrication pinion for gears	PU-lube pinion for gears	PU-lube pinion for chains
	Aluminium, plastic retainer, shaft: steel	Aluminium Halter, Welle: Stahl	Polyurethane-foam open celled axis: steel galvanized or stainless steel	Polyurethane-foam open celled axis: steel galvanized or stainless steel
Lubricant	grease up to NLGI 2	grease up to NLGI 2	oils and greases up to NLGI 2	oils and greases up to NLGI 2
Operating temperature	-20 to +70 °C	-20 to +70 °C	-30 to +150 °C	-30 to +150 °C
Version	segmented	one part two parts three parts four parts	gears: straight sloping right sloping left	Simplex Duplex Triplex

BEKA manufactures lubrication- and hydraulic units according to customer's request. Planning and construction are done according to the customer's specifications.

Oil - air unit and mixing distributor



01-1-10-29 state: 03.13EN

Pictures are exemplary

© BEKA 2013 All rights reserved!

Subject to alterations!

1090200384

Oil - air units

Pictures are in process

Drawing	Type	No. of lubrication points	Metering volume (mm ³ / stroke)	Operating voltage
FAZ03512_00	4086	1 - 6	30 / 60 / 100 / 160	115 V AC
FAZ03519_00				230 V AC
FAZ03692_00				

Oil - air mixing distributor



FAZ01822_02

FAZ02751_01

Drawing	Type	No. of lubrication points	Metering volume (mm ³ / stroke)	Operating press. (bar)		Connection		Press. connection oil - air mixture
				Metering medium	Sprayed air	Metering medium	Sprayed air	
FAZ04057_01	4299	2 / 4 / 6 / 8	10 / 20 / 30 / 50	10 - 50	3 - 6	M10x1	M10x1	pipe Ø 4 (plug-type conn.)
FAZ01822_02	4089	1 - 6	30 / 60 / 100 / 160	10 - 50	1 - 10	G 1/8	G 1/4	pipe Ø 4 or Ø 6
FAZ04185_01	4092	2 - 5	30 / 60 / 100	12 - 50	4 - 8	M10x1	G 1/4	M10x1
FAZ02751_01	4283	2 - 10	50	max. 50	1 - 5	M10x1	M10x1	pipe Ø 2,5 or Ø 4
FAZ03088_00	4089	1 - 6	30 / 60 / 100 / 160	10 - 50	1 - 10	G 1/8	G 1/4	pipe Ø 4 or Ø 6 (plug-type conn.)

Oil reservoir



FAZ03455_00



FAZ01918_03



FAZ03433_02




FAZ03433_00



FAZ03532_00

Model	Type	Reservoir content (l)	Reservoir material
FAZ03455_00	0457	2,5	PA
FAZ01918_03		1,2	
FAZ03433_02		4,2	PE
FAZ03433_00		2	
FAZ03532_00		4	PA



BAIER+KÖPPEL GMBH+CO KG
PRÄZISIONSAPPARATEFABRIK




BEETHOVENSTRASSE 14
91257 PEGNITZ/BAVARIA

PO BOX 13 20
91253 PEGNITZ/BAVARIA

GERMANY

fon +49 9241 729-0
fax +49 9241 729-50

e-mail beka@beka-lube.de
web www.beka-lube.de



Partners

AUSTRIA

BEKA-Lube GmbH
Carola-Blome-Str. 7
5020 Salzburg
fon +43 / 662 / 43 84 40
fax +43 / 662 / 43 84 403
e-mail office@beka-lube.at

BELGIUM

BEKA-LUBE N.V.S.A.
Demerstraat 32
BE 3200 Aarschot
fon +32 / 16 / 64 09 26
fax +32 / 16 / 64 05 48
e-mail bekalube@skynet.be

CANADA

BEKA-LUBE Products Inc.
2830 Argentinia Road, Unit 9
Mississauga ON L5N 8G4
fon +1 / 905 / 821 / 1050
fax +1 / 905 / 858 / 0597
e-mail info@beka-lube.com

Subsidiaries

Argentina
Australia
Belarus
Bosnia
Brazil
Croatia
Czechia
Denmark
Estonia
Finland
Great Britain
Greece
Hong Kong
Hungaria
India
Indonesia
Iceland
Ireland

CHINA

EAST TSANHAIR COMPANY LTD.
7A Building, Medicine Valley No.1,
No.9 Tianfu Street, Bio-Medicine Park,
Zhongguancun Science Park,
Daxing District, Beijing, China 102600
fon +86 / 10 / 83 681 526
fax +86 / 10 / 83 681 520
e-mail beka-lube@bekachina.com

FRANCE

BEKALUBE FRANCE
4, bis Rue de l'Artisanat
89100 Paron
fon +33 / 386 / 83 39 06
fax +33 / 386 / 65 52 24
e-mail contacts@bekalube.fr

ITALY

BEKALUBE s.r.l.
Via Rossi 152
20043 Arcore
fon +39 / 039 / 618 00 88
fax +39 / 039 / 61 75 23
e-mail bekalube@bekalube.it

KOREA

BEKA AHWON
326-1 Danggun Dong
Gunpo Si Kyungki Do Korea
fon +82 / 31 / 451 / 0628
fax +82 / 31 / 451 / 0974
e-mail jhleeahwon@gmail.com

NETHERLANDS

BEKA NEDERLAND B.V.
Wagenmakerij 11
4762 AV Zevenbergen
fon +31 / 168 / 37 15 38
fax +31 / 168 / 33 83 29
e-mail info@beka.nl

SPAIN

BEKA-LUBE IBERICA S.L.
Avda. de Suiza, 3 P.A.L. Coslada
28820 Coslada (Madrid)
fon +34 / 91 / 670 7800
fax +34 / 91 / 670 78413
e-mail beka@beka-lube.es

TURKEY

BEKAMAKS MAKINA SANAYI ve TICARET
LTD. STI. Kucukyali Ticaret Merkezi
B Blok No. 7 Girne Mah.
34852 Maltepe / Istanbul
fon +90 / 216 / 367 34 00
fax +90 / 216 / 367 33 85
e-mail info@bekamaks.com

USA

BEKA-MAX of America
2600 North America Drive Suite 8
P.O. Box 615 West Seneca, NY 14224
fon +1 / 905 / 821 / 1050
fax +1 / 905 / 858 / 05 97
e-mail info@beka-lube.com

