# **Designed for Reliability**

The E-Series pump is a minimum cost, entry level alternative to standard pneumatic pump products. This all-in-one pump package comes complete with no assembly required and is easy to install. All pump packages include high-pressure rupture disk assembly and lube outlet check valve. The E-Series offers many reservoir options for either grease or oil. Great for any application where price is a concern and installation time is at a premium.



# Standard Low Level Switch Options

Uses the same switch kits as many other Trabon® pumps.

## Modu-Flo Reservoirs

Provides easy interchangeability plus compatibility to most Modu-Flo accessories.

# Two Pump Options

Choose from the original fixed output pump or the adjustable output version.

### Drain Valve

Included petcock acts as a grease drain before removing a pump, and an air bleed during initial filling.

Technical Specifications	
Output per Stroke	0.010 to 0.030 in <sup>3</sup> (0.164 to 0.492 cm <sup>3</sup> )
Max Output Pressure	2,000 psi (138 bar)
Ratio	20:1
Reservoir Material	Plastic, cylindrical or rectangular
Air Pressure	40 to 150 psi (2.8 to 10.3 bar)
Cycle Rate	10 CPM grease, 30 CPM oil
Instruction Manual	L13126

### **Typical Fluids**

- Oil up to 30,000 SUS
- Grease up to NLGI #2

### **Typical Applications**

· Presses and other in-plant machines

# >>> Ordering Information

# **E-Series Pump Packages**

Low Level Option		Reservoir Size	Pump Output	Poliof Volvo noi (hor)	Low Level Switch
Included	Not Included	neservoir size	Fullip Output	Relief Valve psi (bar)	Low Level Switch
Grease Packages					
-	563365	3 lb	Fixed	2,000 (138)	563272
563360	-	5 lb	Fixed	1,750 (121)	
563364	563363	6 lb	Fixed	2,350 (162)	563322
_	563370	6 lb	Adjustable	2,000 (138)	003322
_	24N776	12 lb	Fixed	2,350 (162)	

# **EZ Greaser / Grease Jockey Trailer Pump Packages** For fluid grease only (NLGI #0-000)

-	563368	4 lb	Adjustable	Not Included	-
-	563372	10 lb	Adjustable	Not Included	_

# **E-Series Bare Pumps**

Part Number	Pump Output	Pump Output Range per Stroke in3 (cm3)	Relief Valve psi (bar)	Repair Kit
563358	Fixed	0.030 (0.492)	1,750 (121)	563909
563367	Adjustable	0.010 to 0.030 (0.164 to 0.492)	Not Included	563945

# **Air Solenoid Valves**

150 psi maximum pressure, 1/4 in NPT female inlet

Voltage		Air Outlet	Volvo Wovo	Air Motor Action
24 VDC	120 VAC	All Outlet	Valve Ways	Air Motor Action
563332	563315	1/4 in NPSF male banjo	3-way	Single

To create your own custom pump package, combine either of the pump options above with any Modu-Flo reservoir listed on page 69.